08

# **PINCH VALVES**

2/2-way NC, 2/2-way NO, 2/2-way latching Tubing inner diameter 1.6 - 15.0 mm (ID) Tubing outer diameter 4.0 - 19.0 mm (OD)

### **PK Series**



### **NP Series**



# **EPK Series**



# **EL Series**



#### **SPECIFICATIONS**

	PK Series	NP Series	EPK Series	EL Series
Туре	2/2-way NC 2/2-way NO		2/2-way latching	
Tubing inner diameter	1.6 - 6.4 mm		10.0 - 15.0 mm	
Tubing outer diameter	4.0 - 9.6 mm		13.0 - 19.0 mm	
Rated voltage	12 VDC   24 VDC			
Operating pressure	0 - 500 mbar			
Tubing material	Silicone   Pharmed®		Silicone	
Ambient temperature range	0 - 40°C		-10 - 40°C	
Power consumption	10 W		60 W	15 W (when switching)
Operating duration	100% ED			10% ED
Outer dimensions	36.0 x 40.0 x 65.0 - 88.3 mm	36.0 x 40.0 x 64.5 - 87.5 mm	Ø64.0 x 112.0 - 132.0 mm	Ø64.0 x 128.7 - 140.7 mm

The pinch valves can be specially adapted to your tube in order to achieve an optimal closing force.

Customisable to specific requirements (e.g. higher pressure range, different operating mode, higher temperature range, different operating voltage, different port connections, ...)

